

Vmax filter

PDF Download

Download

As part of its separation into a new pure play water company, a new Pentair website has launched. Please visit the new Pentair. This is possible since the V-MAX design offers up to ten times the available filtration media in the same element envelope. It enables purification of solid-contaminated streams, offering high-purity, rapid, single-pass processing, while simultaneously reducing overall operating expense and improving operator ergonomics. In many cases conventional bag filters, stacked disks, and leaf filters can be upgraded to coreless technology. Effective Contaminant Removal The V-MAX coreless elements utilize high-performance media technology to allow very high efficiency removal of contaminants. It is constructed to allow effective use to high differential pressure. Increased Online Life Compared to conventional bag filters V-MAX can offer 3 â€" 5 times longer online life at similar effluent fluid quality. Improved Operating Ergonomics The design of the system enables rapid and easy element installation and replacement. Find Case Studies. List View. The key aspects of an alkylation unit pertain to the amount of acid that needs to be made-up on a continuing basis. This cost becomes even more critical if the plant has no onsite acid regeneration, or the acid consumption exceeds the acid regeneration capacity. Amine Systems. There are a number of factors that affect the capacity and operation of a typical amine system. Solid or liquid contaminants in the system may cause foaming. Reactor products can contain gelatinous, deformable solids form in coating formulation. Batch Process: Limited reactor turn-over constrained through-put due to long filtration process. Reduce operating costs and batch cycle time, double capacity and increase online life. Ethylene Quench Water. Eliminate hydrocarbons in Quench Water system, minimize fouling, provide greater system reliability, lower maintenance, lower energy costs. Silicones are inert, synthetic compounds with a variety of forms and uses. Typically heat-resistant and rubber-like, they are used in sealants, adhesives, lubricants, medical applications, cookware, and insulation. Custody Transfer - Jet Fuel. Product custody transfer involves a number of processes, all of which are intended to meet transfer specifications in terms of water, particulate and metals. Deep Well. Deep Well facilities for the disposal of plant waste streams often employ nominally rated spray spun elements, bags, diatomaceous earth filters, and various other types of conventional filtration technology. The key to optimizing a hydroprocessing unit is to maximize the life of the catalyst bed and increase energy efficiency of the furnaces. Lube Oil Systems. NGLs - Fractionation. There are two basic steps to the treatment of natural gas liquids in the natural gas stream. First, the liquids must be extracted from the natural gas. Second, these NGLs must be separated themselves. Sour Water. Hydrocarbons in the sour water system are typically present on a continuous basis at up to 10, ppm and during upsets to levels greater than 50, ppm. RevZilla will match any advertised price on new merchandise available through another authorized U. Our goal is to provide the best possible shopping experience to every enthusiast who visits RevZilla. You'll also hear about special offers and events! How it works:. Sign in or create an accountto earn ZillaCash on your next purchase with us. Redeem your ZillaCash Rewards on a future order with us! See our customer service page for more details. Universal Fit Parts can be installed on various motorcycles and may require modification. Exact Fit Parts are designed specifically for your bike. Navigation Menu. Wish List. RevZilla offers shipping to your location! Please reference our International Shipping Policy for details. International Shipping Policy. Self-Service Returns. Doesn't fit? Don't love it? Return any unused item within 90 days for a full refund. Start a Return Read our full Return Policy. Lowest Price, Guaranteed. Found it for less? Submit a Price Match. See what our customers are saying about us: Customer Reviews. Zilla Cash Rewards Program. How it works: 1. JavaScript Disabled. We have updated our Privacy Policy. Please click here to review the updates. Fitment Universal Fit parts can be installed on various motorcycles and may require modification. Exact Fit parts are designed specifically for your bike. Filter 0. Clear All Apply. Garage Select a Saved Bike. Select a Bike. No saved bikes? Use the Shop By Bike tool to search for parts that fit your motorcycle. Saved Bikes. Clear All. Out of Stock. Universal Fit Universal Fit parts can be installed on various motorcycles and may require modification. Top Rated. Expand all Collapse all. Image filtering is particularly important when textures in the rendering include very fine detail. For an animated sequence, the choice of image filter can blur pixels to reduce "buzzing" and flickering of detailed textures during playback. When this option is disabled, an internal 1x1 pixel box filter is used. All image samplers support all 3ds Max's standard anti-aliasing filters except the Plate Match filter. Using filters increases rendering time. Doing so might dramatically increase render time as the sampler needs to take additional image samples to resolve the filter. Here is an example briefly demonstrating the effect of different anti-aliasing filters on the final result. Filters are applied on a sub-pixel level, over the individual sub-pixel samples. Therefore, applying the filter at render time produces a much more accurate and subtle result than applying it as a post effect. V-Ray can use all standard 3ds Max filters with the exception of the Plate match filter and produces similar results to the scanline renderer. This example demonstrates the effect anti-aliasing filters have on moire effects in your images. Sharpening filters Mitchell-Netralavli, Catmull-Rom may enhance moire effects, even if your image sampling rate is very high. Blurring filters Area, Quadratic, Cubic reduce moire effects. Note that moire effects are not necessarily a result of poor image sampling. In general, moire effects appear simply because the image is discretized into square pixels. As such, moire effects are inherent to digital images. The effect can be reduced through the usage of different anti-aliasing filters, but is not completely avoidable. The scene is very simple: a sphere with a very fine checker map applied. This is enough to produce quite an accurate approximation to the pixel values. Note that the image looks quite different depending on the filter:. All Rights reserved. Quick Search. V-Ray 5 for 3ds Max. A t tachments 33 Unused Attachments Page History. JIRA links. Skip to end of metadata. Page Contents. Filter Image Zoomed-in image Comments Filtering is off. Image Filter off. Sharp Quadratic. Zoomed-in image. Area filter, size 1. Slightly blurs the image, visually more pleasing than the box filter. Blend filter. Combination of a sharp and a soft filter, kind of dreamy effect. Edge-enhancing filter, often used for architectural visualizations. Note that edge enhancing can produce "moire" effects on detailed geometry. Allows control between edge-enhancement and blurring. Even more edge enhancement; kind of cartoon-style effect. That makes it an even better choice for anglers fishing bigger waters on inch-transom boats such as deep-V hulls, bay boats, flats boats and multi-species craft. Find a Demo Tour. Plasma-fused sleeveless cylinders are lighter and 60 percent harder than steel. They also allow us to enlarge cylinder bores without increasing their dimensions--which creates 4. Yamaha's exlusive In-Bank Exhaust System exits downward through the center of the "V" rather than on the exterior side. Midrange punch and instant throttle response created by Variable Camshaft Timing has to be felt to be believed. Micro-textured cylinder walls increase breathing efficiency while Precision Multi-Point Fuel Injection ensures the precise amount of air and fuel necessary for optimum power and fuel efficiency. Together, they make the 4. A labyrinth exhaust routes gases through a maze before they exit above the water line through an idle exhause relief outlet. This, combined with a mufflerless design, results in unbelievably smooth and quiet operation, with a pleasing sound of power at idle. All Jet model weights include the jet pump assembly weight estimated. Performance that elevates expectations. Find a Demo Tour Owners Manuals. View the hp. Smart Design. Overall Performance. Responsive Throttle. Responsive Throttle Midrange punch and instant throttle response created by Variable Camshaft Timing has to be felt to be believed. Outstanding Fuel Economy. Outstanding Fuel Economy Micro-textured cylinder walls increase breathing efficiency while Precision Multi-Point Fuel Injection ensures the precise amount of air and fuel necessary for optimum power and fuel efficiency. Product Videos. Expand Gallery. Meet the Line-Up. V MAX 4. Super High Output degree 4. Prop Selector. Show More. View Bulletins for all Models. Open box, was a display. All sales final. Read complete description. Skip to main content. Email to friends Share on Facebook - opens in a new window or tab Share on Twitter - opens in a new window or tab Share on Pinterest - opens in a new window or tab. Add to Watchlist. People who viewed this item also viewed. Showing Slide 1 of 1 - Carousel. Check if this part fits your vehicle. Contact the seller. Picture Information. Mouse over to Zoom - Click to enlarge. Trusted seller, fast shipping, and easy returns. Learn more - Top Rated Plus - opens in new window or tab. Get the item you ordered or get your money back. Learn more - eBay Money Back Guarantee - opens in new window or tab. Seller information ironponydirect Contact seller. Visit store. See other items More See all. Item Information Condition:. Sign in to check out Check out as guest. Add to Watchlist Remove from watch list. Watch list is full. Longtime Member. Fast and safe Shipping. This amount is subject to change until you make payment. For additional information, see the Global Shipping Program terms and conditions - opens in a new window or tab. Item location:. Westerville, Ohio, United States. Ships to:. United States and many other countries See details. For additional information, see the Global Shipping Program terms and conditions - opens in a new window or tab This amount includes applicable customs duties, taxes, brokerage and other fees. Estimated between Tue. Delivery times may vary, especially during peak periods. Any international shipping and import charges are paid in part to Pitney Bowes Inc. Learn More - opens in a new window or tab International shipping and import charges paid to Pitney Bowes Inc. Learn More - opens in a new window or tab Any international shipping and import charges are paid in part to Pitney Bowes Inc. Learn More - opens in a new window or tab Any international shipping is paid in part to Pitney Bowes Inc. Learn More - opens in a new window or tab. Related sponsored items. Showing Slide 1 of 2 - Carousel. Report item - opens in a new window or tab. This translation tool is for your convenience only. The accuracy and accessibility of the resulting translation is not guaranteed. Note: The accuracy and accessibility of the resulting translation is not guaranteed. Seller assumes all responsibility for this listing. Iron Pony Direct Closeouts. Visit my eBay store. Sign up for newsletter. Search Store. About Me.

Store Categories. Store home. ITEM : Please read complete listing. We ship M-F, non holidays, 9am-4pm. Please do any research you feel necessary prior to purchasing. Precision-woven, stainless steel, outer-screen construction offers triple-layer protection and increased air flow over stock filter. The "triple-layer protection" contains two epoxy-coated layers of strong steel mesh and one layer of non-woven material. It will last the lifetime of your vehicle with proper care. Washable and reusable , environmentally friendly. Shipping and handling. This item will ship to Ukraine , but the seller has not specified shipping options. Contact the seller - opens in a new window or tab and request a shipping method to your location. Shipping cost cannot be calculated. Please enter a valid ZIP Code. No additional import charges at delivery! This item will be shipped through the Global Shipping Program and includes international tracking. Learn more - opens in a new window or tab. There are 7 items available. Please enter a number less than or equal to 7. Select a valid country. Please enter 5 or 9 numbers for the ZIP Code. Domestic handling time. Taxes may be applicable at checkout. Learn more. Return policy. No returns or exchanges, but item is covered by the eBay Money Back Guarantee - opens in a new window or tab. Payment details. Payment methods. Back to home page Return to top. Back to home page. Listed in category:. Email to friends Share on Facebook - opens in a new window or tab Share on Twitter - opens in a new window or tab Share on Pinterest - opens in a new window or tab Add to Watchlist. Image not available Photos not available for this variation. International Priority Shipping. Sterilizing filtration renders biotherapeutics free of biocontamination. In many cases, sterilizing-grade filters also reduce bioburden or facilitate closed or aseptic processing. They are used to filter active pharmaceutical ingredients APIs , formulated bulk, cell culture media, buffer, additives, process intermediates, and so on. Such applications are often critical for ensuring a successful batch operations. Here, we provide a sizing tool to help you estimate filter-size requirements for simple filtration applications. Specifically, we describe of a simple generic sizing tool K Buf sizing constant for three different sterilizing-grade filters developed using a generic value of permeability for buffer filtration. We include a quick reference chart for different filters to estimate filter-sizing requirements for fairly nonplugging water-like feed streams. Our Vmax technique has been widely used to describe plugging behavior and estimate filter-size requirements of normal-flow membrane filters in biological filtration applications. Using the technique to estimate filter-size requirements involves some experimental filtration work with test materials and membrane filters at constant pressure, followed by simple data analysis. For feed streams, such as buffers, with which plugging is insignificant, membrane permeability becomes the governing parameter for determining filter-size requirements. It can provide a quick estimate of the sterile filter area required to filter a specific volume of buffer for any given pressure and time. Based on the gradual pore-plugging model, the Vmax sizing technique is used to estimate normal-flow filter sizes 1. From the model, we derive Equation 1 for determining the minimum filtration-area requirements for a normal-flow filtration process at constant pressure. In the Vmax method, a constant pressure forces fluid through a filter. As the filter plugs, flow through the filter decreases over time. By performing a small-scale Vmax study with a product, we can obtain data of volume over time and calculate key sizing parameters of the model such as V max and J i. For sterile filtration of plugging fluids e. For nonplugging fluids e. In such cases, Equation 1 may be reduced to Equation 2, which indicates that buffer filtration sizing may be approximated based on membrane filter permeability and process time. Equation 4 implies that fluid viscosity has a direct impact on membrane flux. Fluids of high viscosity may result in lower flux and permeability value. So combining Equations 2 and 5 for a water-like buffer leads to Equation 6. Using Equation 6, we can calculate the minimum filter area required to process a fluid if we know the permeability of the solution for a particular membrane and three process conditions: the batch volume, the process time, and the applied differential pressure applied. We can combine those concepts and express filter permeability and its standard size into a sizing constant, which we refer to as K Buf described below. We extracted and analyzed data from our extensive Vmax filtration-sizing experiments performed by Merck Millipore during process development optimization with nonplugging fluids. We studied three sterilizing-grade filters from Merck Millipore:. We took data points from disposable small-scale scaling devices OptiScale and OptiScale 25 3. All data points were taken from experimental work with buffers commonly used in the industry. Variability from the mean standard deviation â€" observed for each normal curve â€" accounts for the total variability and consisted of membrane variability, solution viscosity variability due to temperature effect, and some measurement errors. An SF of 1. Equation 7 can be used to calculate the number of in. By equating Equation 6 to Equation 7, we derived a sizing constant K Buf Equation 8 and 9 to provide a quick estimate on the number of in. K Buf is the sizing constant applied to water-like, nonplugging buffers for a given filter as expressed in Equation 9. Although data points used to generate K Buf are based on Vmax experimental work on small-scale scaling devices, final filter

configuration at manufacturing scale is a pleated filtration device such as a cartridge or a capsule. Alternatively, a quick reference chart Figure 2 developed using K Buf final constants and filtration time of one hour can be used to estimate filter sizing with reference to applied pressures 5, 10, 15, or 20 psi and batch volume. The K Buf final sizing constants or quick reference charts are applicable for all common buffers with viscosity of 1 cp water-like at room temperature and little risk of membrane fouling. The K Buf sizing method based on K Buf final constants should not be used if the purity and viscosity of a fluid is in doubt. A quick Vmax sizing assessment should be performed in such situations. Merck Millipore application note 5 includes information about the Vmax sizing experiment. To verify the accuracy of filter sizing with the K Buf sizing method, we compared filter area obtained from the K Buf sizing method with the filter area obtained using Vmax analysis. We plotted actual volume against time data collected from Vmax experiments, buffers typically used in biopharmaceutical purifications, and common applied pressures required during production. Common buffers used in industry with water-like behavior include but not limited to sodium hydroxide; all citrates, acetate, chlorides, and Tris buffers; phosphate-buffered saline; hydrochloric acid; and acetic acid. All are limited up to 1M and room temperature. Concentrated solutions will have a viscosity higher than that of water, thereby reducing permeability of solution through a membrane. Table 2 shows comparison of filtration area obtained from the Vmax and K Buf method in three case studies. We calculated the minimum area A min needed for the process using Equation 1, experimental V max and J i , process volume, and a one hour process time for comparing both methods. We would then recommend the final process configuration with the available Merck Millipore filtration devices and calculate the overall SF ratio between the process filter area and the minimum area needed for the process as determined from V max calculations. Filtration sizing with K Buf sizing method: Using appropriate reference chart for a given batch volume and applied pressure at production floor, we can estimate the number of in. The number of cartridges for filtration times apart from one hour should be accounted for accordingly. For example, if the filtration time is two hours, then the number of cartridges would be half the number sized by the reference chart. Conversely, if the filtration time is halved, the process would require twice the number of cartridges. Alternatively, we can estimate the number of cartridges with the equation for K Buf sizing method found in Table 1 for each filter type by applying the batch volume, time, and applied pressure to the equation. Case Study: To filter 5, L of NaHS buffer using a Durapore CVGL filter in one hour at 10 psi applied pressure, two different methods can be used to size the number of cartridges required for processing the volume of buffer. By using our Vmax method performing a small-scale trial the minimum filtration area A min required is 1. Considering an SF of 1. So the actual calculated number of in. Given that a in. Durapore cartridge has an area of 0. The K Buf method also can be used to find the filtration area. Table 2 compares filtration areas sized using the Vmax and K Buf sizing methods. K Buf method sizing results were very similar to those of the Vmax method for the three sterilizing-grade filters. The above discussion and comparative data analysis indicate that the K Buf sizing method provides a reasonable approximation of sterile filter sizing for buffer filtration applications. Other sterilizing-grade filters or small-scale devices may not provide similar sizing results because of a difference in membrane permeability and device scaling factors 3. The K Buf sizing method can be applied only for nonplugging solutions at room temperature with viscosities similar to that of water. Plant piping such as elbows and valves, head pressure due to elevation of filters or tanks, and other restrictions such as housing design e. Additional safety factors or increasing applied pressure to a filter assembly to increase effective pressure across a filter may be considered to overcome the effect of system and piping losses 8. To ascertain the application of the K Buf sizing method to viscous nonplugging solutions, more experimental data must be generated to to verify the effect of fluid viscosity. A simple sizing method K Buf has been developed and shown to closely approximate filter-sizing requirements for sterile buffer-filtration applications. The overall safety factors, around filtration area, ranged from 1. The method provides a good estimate of the filtration area required for buffer filtration. Figure Table 1: Sizing constants and formula for sterilizing-grade filters. Lenchi, RW, and S. Membrane Sci. Giglia, S. Lutz, H. Scaling from Disc to Pleated Devices. PDA J Pharm. Brown, AI. Membrane Pleating Effects in 0. Royce, J, and R. Home Products Finder. Quick Links. Products Product Calculator. View the entire collection of mounting brackets, junction boxes and specialty mounting accessories. Product Selector. Product Demos. Elevated Skin Temperature Products. EST System. EST Camera. EST Blackbody. IP Products. Compare up to 4 models. Showing: 1 - of Matching. Page 1 of 1. Filter Your Results. Show all. Rack mount ears Pole mount bracket for bullets and dome cameras. Ceiling mount and junction box. Ceiling mount and junction box for fixed lens dome camera with video analytics. Ceiling mount and junction box for turret cameras. Ceiling mount and junction box for V8 analog dome cameras.

Ceiling mount and junction box for varifocal lens dome camera with video analytics. Ceiling mount bracket. Ceiling mount bracket - white. Ceiling mount bracket for multi-sensor cameras. Ceiling mount bracket for V1 outdoor dome cameras. Ceiling mount bracket for V7 outdoor dome cameras. Ceiling mount bracket for vandal ball cameras. Converter plate for electronic gang box - ivory. Converter plate for electronic gang box - white. Corner and pole mount bracket. Corner and pole mount bracket - white. Corner mount bracket for outdoor dome cameras. Decorative rings for V7 ultra low-profile vandal dome cameras. HD Video Balun Converter. Infra red iluminator for panoramic bullet, ft. Junction box. Junction box - white. Junction box for bullet camera with video analytics. Junction box for bullet cameras. Junction box for bullet cameras- White. Junction box for fixed lens dome camera with video analytics. Junction box for outdoor dome cameras. Junction box for panoramic bullet. Junction box for turret cameras. Junction box for V7 outdoor dome cameras. Junction box for V8 analog dome cameras. Junction box for vandal ball cameras. Junction box for varifocal lens dome camera with video analytics. Looping output - 8 channels. Micro dome angle mount bracket. Micro dome surface mount bracket. Micro dome trim rim - black

d2cg york wiring diagram
1976 ford f100
98 honda civic under hood fuse box

, Micro dome trim rim - blue. Micro dome trim rim - green. Micro dome trim rim - red. Parapet mount bracket. PoE switch - 4 channels. PoE switch - 8 channels. Pole mount bracket for bullet cameras. Pole mount bracket for outdoor dome cameras. Rack mount ears 19". System Control Keyboard. Wall mount and junction box. Wall mount and junction box for fixed lens dome camera with video analytics. Wall mount and junction box for varifocal lens dome camera with video analytics. Wall mount bracket - white. Wall mount bracket for indoor dome cameras. Wall mount bracket for multi-sensor cameras. Wall mount bracket for outdoor dome cameras. Wall mount bracket for V7 outdoor dome cameras. Wall mount bracket for V8 analog dome cameras. Wall mount bracket for V9 outdoor dome cameras. Wall mount bracket for vandal ball cameras. Wall mount for fixed lens turret cameras. Wall mount for varifocal turret cameras. DW Spectrum Mobile for v2. HD video balun converter. Indoor Dome. Outdoor Dome. Vandal ball.